



Energetic Lighting’s LED flat panel light fixture provides options for color output with sensor and emergency battery backup options. Available in standard 2x2 configuration and suitable for any office application or layout. This panel light can be used for general office lighting, providing high quality light without any of the maintenance issues associated with fluorescent tubes. Installation is quick and simple when mounting into standard drop-in T-grid suspended ceiling systems. Anchor points at each corner are also provided for suspended cable mounting as well hooks for seismic code compliance. Options include an integrated microwave occupancy sensor as well as emergency battery backup system with standard 90 minute runtime. Constructed with a durable steel rear panel, extruded aluminum frame, and an LED lifetime rating of at least 50,000 hours, this panel is designed for many years of reliable operation.

Features

- Dimmable with 0-10v systems
- Suitable for Damp Location use
- Standard T-Grid drop ceiling installation
- 120-347 high-voltage version available
- Suitable for Type IC installation

Applications

- Architectural decor
- Overhead task lighting
- Ambient room lighting
- General lighting

Specification

Order Number
Model Number
Configuration
Body Color/Finish
Beam Angle
Lumen Output
Luminous Efficacy
Input Power
Input Voltage
Power Factor
THD
Color Temp (CCT)
Color Rend (CRI)
Lifetime Rating
Warranty
Dimmability
Operating Temp
Environment
DLC
Energy Star
Safety Cert
Weight
Dimensions

Dimensions and Packaging Info

Model Number
Item UPC
Case UPC
Master Carton UPC
Item(s) per pack
packs per case
Case per Master
Item weight
Case weight
Master Weight
Item pack dimensions
Case dimensions
Master dimensions