



Energetic Lighting’s LED Vapor Tight fixture radiused profile with a nominal lumen output of 5100 lumens, while drawing only 40 watts of power. The fully sealed housing can be installed in high humidity areas and locations that receive direct water exposure. Both fixture body and diffuser are constructed of durable polymers for impact resistance. This versatile light can be used for general functional lighting, where its rugged construction and long LED lifetime will provide years of maintenance free service. Installation is quick and simple with standard trade size conduit openings at both ends, and quick mounting adapters.

Features

- Complete annular gasketing
- Modern and efficient design
- Ribbed translucent diffuser
- Suitable for Wet Location use
- Easy and secure installation

Applications

- Impact resistant applications
- Wet environments
- Parking and Garage lighting
- General lighting

Specification

Order Number
Model Number
Configuration
Body Color/Finish
Beam Angle
Optical Distribution
Lumen Output
Luminous Efficacy
Input Power
Input Voltage
Power Factor
THD
Color Temp (CCT)
Color Rend (CRI)
Lifetime Rating
Warranty
Dimmability
Operating Temp
Environment
DLC
Energy Star
Safety Cert
Weight
Dimensions

Dimensions and Packaging Info

Model Number
Item UPC
Case UPC
Master Carton UPC
Item(s) per pack
packs per case
Case per Master
Item weight
Case weight
Master Weight
Item pack dimensions
Case dimensions
Master dimensions