



Energetic Lighting offers a complete line of LED R and BR style bulbs with formats for R20, BR30, and BR40 profiles, providing an environmentally friendly alternative to traditional incandescent bulbs. These energy efficient LED bulbs operate at less than 1/6th the wattage of its incandescent equivalent, while delivering the same light output. These bulbs are suitable for damp location installation and fully dimmable down to 10%. This bulb will provide a reliable light source for at least 25,000 hours while being backed by a 5 year warranty.

### Features

- No UV or IR radiation
- Elegant and efficient design
- Mercury-free construction
- 120° beam spread light profile

### Applications

- General lighting
- Damp Location Installation
- Ambient lighting

### Specification

Order Number	11007
Model Number	E3B414D-850-VB
Beam Angle	120°
Optical Distribution	
Lumen Output	1100 LM
Luminous Efficacy	79 LM/W
Input Power	14 W
Equivalent Wattage	85
Input Voltage	120 Vac
Power Factor	>0.9
THD	
Color Temp (CCT)	5000 K
Color Rend (CRI)	780
Lifetime Rating	25000 hours
Warranty	5 Years
Dimmability	Dimmable to 10%
Operating Temp	-4 to 113 (°F)
Environment	Damp Location
Enclosed Install	No
DLC	
Energy Star	Energy Star
Safety Cert	UL
Weight	0.88 LBS
Dimensions	6.30"(L)x 4.73"(d)
Base Type	E26

### Dimensions and Packaging Info

Model Number	E3B414D-850-VB
Item UPC	8 4594000523 0
Case UPC	10 8 4594000523 7
Master Carton UPC	20 8 4594000523 4
Item(s) per pack	1 bulb per pack
packs per case	4 packs per case
Case per Master	8 case per master carton
Item weight	1 lb
Case weight	4.5 lbs
Master Weight	38 lbs
Item pack dimensions	5.7"(w) x 5.7"(l) x 7.2"(h)
Case dimensions	12.5"(w) x 12.5"(l) x 8"(h)
Master dimensions	26"(w) x 26"(l) x 17"(h)