



Energetic Lighting's™ E2FMC fixture is designed to emulate the look and feel of traditional circline fluorescent tube flushmount fixtures, but operate at a significantly lower wattage. Installation is quick and simple when mounting into standard ceiling junction boxes, and may be installed on circuits with standard wall dimmers. Constructed with a durable housing body and LED lifetime rating of at least 50,000 hours, this rugged flushmount is designed for many years of reliable operation.

Features

- Durable white polymer diffuser
- Brushed stainless steel accent design
- Mercury-free construction
- Suitable for Damp Location use
- Easy and secure installation
- TRIAC Dimmable

Applications

- Architectural decor
- Overhead task lighting
- Ambient room lighting
- General lighting

Specification

Order Number	40008
Model Number	E2FMC15-840
Beam Angle	110°
Optical Distribution	
Lumen Output	1600 LM
Luminous Efficacy	73 LM/W
Input Power	22 W
Input Voltage	120 Vac
Power Factor	0.99
THD	<0.2
Color Temp (CCT)	4000 K
Color Rend (CRI)	84
Lifetime Rating	50000 hours
Warranty	5 Years
Dimmability	Triac dimmable
Operating Temp	-4 to 104 (Å°F)
Environment	Damp Location
Energy Star	Energy Star
Weight	2.5 LBS
Dimensions	14.5"x14.5"x3"
Safety Cert	UL

Dimensions and Packaging Info

Model Number	E2FMC15-840
Item UPC	8 4594000630 5
Case UPC	10 8 4594000630 2
Master Carton UPC	
Item(s) per pack	1 fixture per package
packs per case	4 packs per case
Case per Master	
Item weight	3 lbs
Case weight	16 lbs
Master Weight	
Item pack dimensions	5.25 (L) X 4.5 (W) X 4.25 (H)
Case dimensions	21 (L) X 18 (W) X 17 (H)
Master dimensions	