



Energetic Lighting's E2WR and ELYWL series LED surface mount wraps showcase a soft fixture form factor while delivering up to 4200 lumens in their 4-ft length, while drawing only 40 watts of power. These versatile lights can be used for general room lighting, or as a functional work area lights with an all white or silve accent appearance. Installation is quick and simple when mounting into standard ceiling junction boxes. Constructed with a durable steel housing body and LED lifetime rating of at least 50,000 hours, these rugged wrap lights are designed for many years of reliable operation.

**Features**

- Different appearance options
- Modern and efficient design
- Reduced glare translucent diffusers
- Suitable for Damp Location use
- 0-10V dimming on E2WR model

**Applications**

- Architectural decor
- Overhead task lighting
- Ambient room lighting
- General lighting

**Specification**

| Order Number         | 30025           | 30027           | 30023           |
|----------------------|-----------------|-----------------|-----------------|
| Model Number         | ELYWL2-302C     | ELYWL2-302S     | ELYWL2-301C     |
| Beam Angle           | 110°            | 110°            | 110°            |
| Optical Distribution |                 |                 |                 |
| Lumen Output         | 2100 LM         | 2100 LM         | 4356 LM         |
| Luminous Efficacy    | 105 LM/W        | 105 LM/W        | 109 LM/W        |
| Input Power          | 20 W            | 20 W            | 40 W            |
| Input Voltage        | 120-277 Vac     | 120-277 Vac     | 120-277 Vac     |
| Power Factor         | >0.9            | >0.9            | 0.93            |
| THD                  | <0.2            | <0.2            | 0.11            |
| Color Temp (CCT)     | 4000 K          | 3000 K          | 4000 K          |
| Color Rend (CRI)     | >80             | >80             | >80             |
| Lifetime Rating      | 50000 hours     | 50000 hours     | 50000 hours     |
| Warranty             | 5 Years         | 5 Years         | 5 Years         |
| Dimmability          | No              | No              | No              |
| Operating Temp       | 14 to 122 (°F)  | 14 to 122 (°F)  | 14 to 122 (°F)  |
| Environment          | Damp Location   | Damp Location   | Damp Location   |
| DLC                  |                 |                 | DLC Standard    |
| Weight               | 6.1 LBS         | 6.1 LBS         | 6.1 LBS         |
| Dimensions           | 24.3"x5.6"x2.0" | 24.3"x5.6"x2.0" | 48.5"x5.6"x2.0" |
| Safety Cert          | UL              | UL              | UL              |