

# LED Pro Classical High Bay

Please read and understand this entire manual before attempting to assemble, operate or install the product. Failure to do so could lead to electric shock, fire or other injuries that could be hazardous or even fatal.



Be sure the electricity to the wires you are working on is shut off. Either remove the fuse or turn off the circuit breaker.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This product must be installed in accordance with local, state and national electrical codes.


Installation work shall be completed by a licensed installer that is familiar with the construction and operations of the product.

## Diffuser Assembly Procedure




1. Align the three keyhole mounting slots on the mating face of the diffuser flange to the fixture body around the LED array.
2. Lock the three screws through the keyhole slots and tighten down the screws to secure the diffuser.

## Mounting instructions




Picture 1

1. Hang the fixture to ceiling mounting hook, un-hinge safety hook and latch onto a separate hook or building structure. Loosen two screws on wiring compartment but do not remove



Picture 2

2. Slide the wiring compartment enclosure so that wiring can be accessed. Connect building leads to fixture within wiring compartment.




Picture 3

3. Swing fixture body back up and secure the wiring compartment enclosure by re-tightening the two screws from step 2.

### NOTES:

- Make sure the luminaries are installed and fitted by a qualified electrician ensuring the installation complies to the current National Electrical Code and all local codes.
- Ensure all electrical connections are secure & that there are no loose strands.
- This is a Class I product and must be earthed.
- Install the fitting in a well-ventilated environment, keep away from corrosive/explosive materials, flammable gas or electric dust.
- Violent shaking or impact should be avoided when the fitting is working.
- Make sure that the fixings are adequate to support the weight of the fitting.
- Before installation or maintenance, turn off electric power and allow the fitting to be cool.

### WIRING INSTRUCTION OF MAIN CABLE:



### WARNING:

The product must be grounded and installed in accordance with the National Electrical Code and all local codes. Failure to do so may increase the RISK OF PERSONAL INJURY, PROPERTY DAMAGE, FIRE AND DEATH